

## CDQR4 - CYLINDER QUICK RELEASE COUPLING



The CDQR4 cylinder quick release coupling incorporates a unique spring action combined locking system (patent pending).

This dual purpose coupling offers a new way in which to mount your wing system to twin or single cylinder configurations. This unit can also be used to mount a pony tank and/or torch battery housing.

Fitting is straightforward. With the additional fittings provided, mount the male or female part of the coupling in the middle of your twin-set via the bolts that secure your stainless steel cylinder twinning bands. Alternately, mount your single tank via cam bands or stainless steel 'jubilee' bands (not included). The other half of the coupling is attached to the wing system by using the bolt kit provided.

Next, simply sleeve the coupling together. Before mating the couplings together, lift the locking pin handle and, once fully mated, release and ensure that the couplings are locked together. Now screw the pull handle clock-wise so the system is fully locked.

This coupling is particularly useful when mixing and matching cylinder sets for different gas mixes and when refilling. Additional male or female fittings are available separately for this reason.

Various sized cam bands and stainless steel 'jubilee' bands are available as accessories. Checkout our bands section on our website.

### CDQR4

Contents: Male & female coupling & bolt kit manufactured from marine grade stainless steel.

Bracket size: 390 x 44 x 22mm.

Total Weight inc bolt kit: 0.9kgs.

CODE	DESCRIPTION
CDQR4	CYLINDER Q/R COUPLING COMPLETE
CDQR4M	MALE Q/R COUPLING ONLY (0.35kgs)
CDQR4F	FEMALE Q/R COUPLING ONLY (0.45kgs)

## CDQR5 - QUICK RELEASE COUPLING



These quick release couplings are specially designed to give the diver easier mounting of equipment. The smaller size, CDQR5, is mainly used to mount pony/Argon tanks and/or torch battery housing and light enough for mounting equipment to helmets.

The male half of the coupling may be fixed by bolts through the M6 holes for mounting to a flat surface or via the slots with stainless steel 'jubilee' bands (not included).

The female half of the coupling may be mounted via the slots utilising stainless steel 'jubilee' bands (not included).

The coupling has a spring lever lock and once the couplings are sleeved together this automatically locks the two halves. To release simply depress the lever to detach.

Various sized stainless steel 'jubilee' bands are available as accessories. Checkout our bands section on our website.

### CDQR5

Contents: Male & female couplings, materials are manufactured from marine grade stainless steel.

Bracket size: 90 x 42 x 20mm.

Total Weight: 0.20kgs.

CODE	DESCRIPTION
CDQR5	QUICK RELEASE COUPLING COMPLETE
CDQR5M	MALE Q/RELEASE COUPLING ONLY (0.07kgs.)
CDQR5F	FEMALE Q/RELEASE COUPLING ONLY (0.13kgs.)